

COAXIAL CABLE

MATV APPLICATIONS

Construction

Applications:

- Suitable for RF signal transmission.
- MATV.

Packaging:

- 1000 ft spools.



311



311A



311B



311C

CUSTOM CATALOG NUMBER	SIZE	INSULATION CORE	SHIELD COVERAGE	NOMINAL O.D.	NOM. CAP. (pF/ft)	VEL. OF PROP. (%)	NOM. IMP. (Ω)	NOMINAL ATTENUATION		NOMINAL WEIGHT
	AWG/MCM	INCHES		INCHES				MHz	DB/100 FT	LBS/MFT
311 RG11 A/U	18 AWG (7/26) Tinned Copper	Solid Polyethylene	95% Bare Copper Braid	Black PVC	20.9	66	75	50	1.5	100
								100	2.1	
								200	3.2	
								400	4.7	
		1000		8.0						
311A RG11 A/U	18 AWG (7/26) Tinned Copper	Solid Polyethylene	95% Bare Copper Braid	Black Non-Contaminating PVC	20.9	66	75	50	1.3	95
								100	2.0	
								200	2.9	
								400	4.2	
		700		5.8						
		900		6.8						
311B RG11/U	14 AWG Solid Bare Copper	Cellular Polyethylene	95% Bare Copper Braid	Black Polyethylene	18.4	78	75	50	1.0	88
								100	1.5	
								200	2.2	
								500	3.7	
		900		5.2						
311C RG11/U Triaxial	14 AWG Solid Bare Copper	Cellular Polyethylene	95% Double Bare Copper Braid	Black Polyethylene	17.3	78	75	50	1.0	127
								100	1.5	
								200	2.2	
								400	3.3	

R

Custom Cable Corp.



Recognized Component
Underwriters Laboratories Inc.

OSHA Acceptable
Occupational Safety and Health Administration

242 Butler Street • Westbury, New York 11590-3193 • Tel: (516) 334-3600 • Toll Free: (800) 832-3600 • FAX: (516) 334-3989

www.customwireandcable.com • email: sales@customwireandcable.com